




CMV2000
AREA SCAN SENSORS



The CMV2000 is a high sensitivity, pipelined global shutter CMOS image sensor with 2048 x 1088 pixel resolution

capable of HD format. Pipelining allows exposure during read out. The state-of-the-art pixel architecture offers true correlated double sampling (CDS) reducing the fixed pattern noise and dark noise significantly. The imager integrates 16 LVDS channels each running at 480 Mbps resulting in a 340 fps frame rate at full resolution at 10 bit per pixel. Driving and read-out are programmed over a serial peripheral interface. An internal timing generator produces the signals needed for read-out and exposure control of the image sensor. External exposure triggering remains possible. A 12 bit per pixel mode is available at reduced frame rate.

SPECIFICATIONS

Part status	Production
Resolution	2MP - 2048 (H) x 1088 (V)
Pixel size	5.5 x 5.5
Optical format	2/3"
Shutter type	Global shutter
Frame rate	340 fps (10 bit) 70 fps (12 bit)
Output interface	16 LVDS outputs @ 480 Mbps
Sensitivity	5,56 V/lux.s
Conversion gain	0,075 LSB/e-
Full well charge	13500 e-
Dark noise	13 e- (RMS)
Dynamic range	60 dB
SNR max	41,3 dB
Parasitic light sensitivity	1/50000
Extended dynamic range	Yes, up to 90 dB
Dark current	125 e-/s (25 °C)
Fixed pattern noise	< 1 LSB (<0,1% of full swing)
Chroma	Mono and RGB
Supply voltage	1,8V / 3,3V
Power	600 mW
Operating temperature range	-30 to +70 degC
RoHS compliance	Yes
Package	Ceramic 95 pins μ PGA/LGA or 92-pins LCC
Socket	Andon Electronics (http://www.andonelectronics.com) 679-92-SM-G10-L14-1 (LCC) 10-12-06-095-400T4-R27-S14 (PGA, thru-hole) 10-12-06-095-414T4-R27-S14 (PGA, surface mount)

ORDERING INFO - CMV2000

Part Number	Version	Chroma	Microlens	Package	Glass
CMV2000-3E5M1PP	version 3	mono	Yes	ceramic 95pins μ PGA	plain
CMV2000-3E5C1PP	version 3	RGB Bayer	Yes	ceramic 95pins μ PGA	plain
CMV2000-3E12M1PP	version 3	mono - NIR enhanced (12 μ m epi)	Yes	ceramic 95pins μ PGA	plain
CMV2000-3E5M1LP	version 3	mono	Yes	ceramic 95pins LGA	plain
CMV2000-3E5C1LP	version 3	RGB Bayer	Yes	ceramic 95pins LGA	plain
CMV2000-3E12M1LP	version 3	mono - NIR enhanced (12 μ m epi)	Yes	ceramic 95pins LGA	plain
CMV2000-3E5M1CA	version 3	mono	Yes	ceramic 92pins LCC	double-side AR coated
CMV2000-3E5C1CA	version 3	RGB Bayer	Yes	ceramic 92pins LCC	double-side AR coated
CMV2000-3E12M1CA	version 3	mono - NIR enhanced (12 μ m epi)	Yes	ceramic 92pins LCC	double-side AR coated
CMV2000-3E5M1PN	version 3	mono	Yes	ceramic 95pins μ PGA	removable